

ACO ACCESS


INSTALLATION DRAWING



DRWG# XA1P-AP1

Pavermate Access Cover: Pavers 1

www.acoaus.com.au

for 330kg Nominal Wheel Load**NOTES:**

1. Specific site conditions may require an increase in these dimensions or reinforcement. It is the customer's responsibility to ensure the concrete encasement is designed for the application. *Engineering advice may be required.*
2. A minimum concrete strength of 25MPa is recommended. The concrete should be vibrated to eliminate air pockets.
3. The finished level of the concrete surround must be flush with the top of the frame.
4. 45mm minimum thickness of concrete must be set into the base of the cover prior to pouring concrete surround.
5. The paver course adjacent to the frame edge must be fully bonded to the concrete surround.
6. Refer to ACO's latest installation instructions for complete details.

ACO ACCESS

SPECIFICATION CLAUSE

ACO Polycrete Pty Ltd
 134-140 Old Bathurst Road
 Emu Plains NSW 2750
 Tel: +61 2 4747 4000
 Fax: +61 2 4747 4060
 e: technical@acoaus.com.au

DRWG# XA1P-AP1

Pavermate Access Cover

www.acoaus.com.au

All access covers & frames are to be ACO Access Pavermate (for 330kg nominal wheel load). Covers are manufactured from steel of minimum thickness 2mm and galvanised to AS 4680. Covers are to be fitted with a polyethylene gas & water seal and contain 4 high tensile steel M16 bolts. For sizes, part nos. & configurations refer to Drawing/ Table No. _____ *

Pavermate covers are to be filled with concrete to a depth of 45mm with a minimum compressive strength of 32 MPa at 28 days, and minimum cement content of 400kg/m³.

* Please delete or complete where appropriate.